



Monochrome Terminal Adapter 12065

Display Features:

Use VGA or LCD Flatscreen
26, 44 or 49 lines with top
and / or bottom status lines,
80 characters per line,
10 page memory,
variable screen scroll,
programmable tab stops,
double high / wide characters,
flicker free refresh rate,
selectable screen saver,
IBM PC character set,
stable case as monitor stand,

Accessories:

Calculator
Monthly calendar
Clock with alarm setting
ASCII and diagnostic chart

Environmental:

Temp. Operating 10°C to 40°C
Altitude 0 to 3,048m
Humidity non condensing
30 to 80% RH
Temp. Storage 0°C to 50°C
Humidity non condensing
0 to 95% RH
Fanless, convection cooling

Communication:

RS-232C Serial host port
110 up to 134.4 k baud
Full / half duplex
Local block
Monitor Mode
DTE, DB 25 female socket

Auxiliary RS-232C serial port
up to 38.4 k baud, bidirectional
DCE, DB 25 female socket

Parallel printer port
IBM PC, Centronix compatible

PS2 Keyboard Connector
up to 35 programmable keys

Options:

Ethernet 10Base T TCO/IP
RS-422, Current Loop

UPIC GmbH

Schwarzwaldstrasse 9
D 63811 Stockstadt / Main
Germany
Fon: +49 6027 1255
Fax: +49 6027 3565
email: info@upic.de
www.new-terminal.de

Emulations:

ADDS Viewpoint
AT 386
PCTerm
SCO Console
TVI 925
VT 100, VT 220, VT 320
Wyse 50, 50+, 60

Physical Characteristics:

Weight 2.0 kg
Height, Length, Width (cm)
30.0 x 30.0 x 6
Packing, Weight 2.4 kg
Height, Length, Width (cm)
42.0 x 42.0 x 12.0

Power:

Universal power supply
90 – 264 V AC, 47 – 63 Hz
0.5A – 0.2A max. (operating)

Approvals:

UL
TÜV
FCC-A
CE
DHHS
VCCI