



Universal Text Terminal 12060

Display:

14 inch high resolution flat screen with reduced glare, bezel to bezel overscan, 26, 30 or 52 lines with top and/or bottom status lines, 80 or 132 characters per line, 10 page memory, variable speed smooth scroll, selectable refresh rate 60, 71, 82 and 100 Hz, double high / wide characters, clear flicker free viewing, white phosphor, optional choice of green and amber, selectable screen saver, mounted tilt and swivel base,

Accessories:

Calculator
Monthly calendar
Clock with alarm setting
ASCII and diagnostic chart

Environmental:

Temp. Operating 10°C to 40°C
Altitude 0 to 3,048m
Humidity non condensing
30 to 80% RH
Temp. Storage 0°C to 50°C
Humidity non condensing
0 to 95% RH
Fanless, convection cooling

Communication:

RS-232C Serial host port
110 up to 134.4 k baud
Full / half duplex
Local block
Monitor Mode
DTE, DB 25 female socket

Auxiliary RS-232C serial port
up to 38.4 k baud, bidirectional
DCE, DB 25 female socket

Parallel printer port
IBM PC, Centronix compatible

PS2 Keyboard Connector
up to 35 programmable keys

Options:

Ethernet 10Base T TCO/IP
RS-422, Current Loop

UPIIC GmbH

Schwarzwaldstrasse 9
D 63811 Stockstadt / Main
Germany
Fon: +49 6027 1255
Fax: +49 6027 3565
email: info@upic.de
www.new-terminal.de

Emulations:

ADDS Viewpoint
AT 386
BBS ANSI
SCO Console
TVI 925
VT 100, VT 220, VT 320
Wyse 50, 50+, 60

Physical Characteristics:

Weight 10.8 kg
Height, Length, Width (cm)
34.0 x 33.0 x 31.8
Packing, Weight 11.4 kg
Height, Length, Width (cm)
53.4 x 53.4 x 40.6

Power:

Universal power supply
90 – 264 V AC, 47 – 63 Hz
0.5A – 0.2A max. (operating)

Approvals:

UL, cUL
TÜV
FCC-B
CE
MPR-II
DHHS
VCCI

Unique Products Int.l Commerce

These specification may change
without prior notice.

All trademarks are the property of the
respective owners